



TREATMENT FORMULA

Sure Grip Floor Safety Treatment features a revolutionary new process that molecularly alters the surface of ceramic tile, quarry, concrete and other mineral flooring increasing the co-efficient of friction (COF). The most important feature of this treatment is the dramatic increase of traction when the floor surface is subject to water or liquid spills.

- Increases traction under wet conditions
- Part of a complete floor safety program
- Lasts up to 3 years with proper maintenance
- Will meet OSHA and ADA guidelines for floor safety

Recommended uses:

- All mineral flooring including:
 - Slate
 - Quarry
 - Terrazzo
 - Ceramic
 - Brick
 - Concrete and others.
- Porcelain Tubs

DO NOT USE ON ANY SURFACE WITH FLOOR FINISH, SEALER OR WAX.

Dilution Ratios:

Use Full Strength

Data

Data	
Product Name:	Treatment Formula
Appearance:	Blue
Odor:	Pungent
Ph in use dilution:	4.20
DOT Hazardous ingredients:	Ammonium Biflouride/Hydrochloric Acid
Vapor pressure (mm/hg):	N/A
Boiling point, F:	38.0555 °C
Solubility in water:	Complete
Flash Point:	>101°C

EMERGENCY AND FIRST AID PROCEDURES:

INGESTION- give large amounts of water or milk; do not induce vomiting; get medical attention

INHALATION- remove patient to fresh air source

SKIN CONTACT- flush with water for 15 minutes; if redness appears, get medical attention

EYE CONTACT- flush with water for 15 minutes; get medical attention.

For complete application instructions or if you have any questions or concerns please go to our website www.SureGripFloors.com or contact us at 1-800-928-6281